## ) tersano

terra [earth/land], sano [healthy]

### **Changing** The Way The World **Cleans**



CERTIFIED · PROVEN · POWERFUL



### The Tersano Advantage

#### **POWERFUL**

*More effective than bleach and over 50% stronger.* \* \*50% *claim based on comparison of "Oxidation Potential Ratings"* 

**COST SAVINGS** Save up to 50% vs using chemicals.

**SAFER** Non-irritant, non-caustic, no fragrance added, and antimicrobial.

#### **ENVIRONMENTALLY RESPONSIBLE**

Breaks down to water and oxygen once it's finished working.

#### **THE SMART CHOICE**

*For your staff and customers - improved customer satisfaction, no personal protective equipment - one solution for all needs.* 

#### **INTERNATIONAL DISTRIBUTION**

lotus<sup>®</sup> PRO is currently used in over 10 countries across the globe.

#### Key sectors currently using Tersano

#### School Districts

- Hotels
- Universities
- Restaurants
- Airports
- Retail Stores
- Manufacturing
- Food Services
- Health Care Facilities
- Government Agencies



#### The **Power** of **Stabilized Aqueous Ozone** The **perfect** combination that **cleans** & **sanitizes**

Ozone is created naturally when sunlight or lightning adds an extra oxygen atom to oxygen molecules in the air. Some of this ozone is then infused into raindrops, resulting in aqueous ozone (AO). Ozone has long been used in water treatment, food sterilization and general sanitation for its remarkable anti-viral and anti-fungal properties.

With the lotus® PRO technology, stabilized aqueous ozone is created when introducing an extra oxygen atom to an oxygen molecule and water molecules. This combination creates a highly effective cleaning agent that breaks down dirt, grease, and other contaminants, safely replacing traditional chemical cleaners and pathogen-reducing sanitizer.

#### **Regulatory Compliance**

Onsite production of electrolyzed water is considered by the U. S. Environmental Protection Agency (USEPA) to be a pesticidal device and is subject to the requirements specified in 40 CFR 152.500. Tersano meets those requirements by producing aqueous ozone.

The use of aqueous ozone generated by our lotus<sup>®</sup> PRO products are subject to strict regulatory requirements under many government agencies including the Environmental Protection Agency (EPA), the Food and Drug Administration (FDA), the US Department of Agriculture (USDA) and the Department of Labor Occupational Safety and Health Administration (OSHA).

#### **3** SIMPLE **STEPS**



STEP 1 Inside the lotus<sup>®</sup> PRO unit, oxygen from the air is safely turned into ozone then infused into ordinary tap water.



Ozone is attracted to germs, soils and bacteria and quickly eliminates contaminants it comes in contact with



STEP 3 The lotus<sup>®</sup> PRO system works for hours, after which point it converts back into water and ozygen.

#### lotus® PRO Regulatory Information

EPA Site Registration No.: 89093-CAN-001

CSA: Tested to CSA Standard E60335-1/4E:03 by TUV

UL: Tested to UL Standard 979 by TUV

Europe: CE and EN 60335-1/A2:2006 compliant

ASSE: Tested to ASSE Standard 1055-2009 by CSA Group

FDA Safe Designation: 21CFR184.1563

NSF International Registration No.: 152236



EPA: DIS/TSS-4 sanitizer (food contact surface)

OSHA: Off-gas O3 < .01 ppm PEL

**GREEN SEAL:** This device-generated solution meets Green Seal<sup>™</sup> Standards GS-37 and GS-53 based on effective performance, concentration of product, minimized packaging, and protective limits on VOCs and human & environmental toxicity. GreenSeal.org

#### Where to use it?

#### **lotus**<sup>®</sup> **PRO** technology for **extended sanitizing power**

As a natural all-purpose cleaning and sanitizing agent, the lotus® PRO is being used in universities, factories, hospitals, office buildings, hotels and retail stores all over North America and Europe to clean and sanitize with stabilized aqueous ozone instead of cleaning chemicals.





#### **APPLICATIONS**

- Flooring, hardwood, tile, vinyl surface Showers, bathtubs, toilets, sinks
- Carpet
- Concrete, terrazzo, & stone
- Bathroom & kitchen counters
- Glass, mirrors, stainless steel, chrome surfaces
- Handrails, escalators, elevators
- Shelving, desks, tables, chairs
- Lab equipments
- Appliances
- Fruits & vegetables

Fill trigger sprayers, mop buckets and auto scrubbers.




# How **lotus<sup>®</sup> PRO** works

# lotus<sup>®</sup> PRO High Capacity Unit with Stabilization Module

bottles, mop buckets, and auto scrubbers - killing germs\* while cleaning. It provides residue-free performance for a powerful natural cleaner and sanitizer. The aqueous ozone is made on demand with continuous flow for spray The lotus<sup>®</sup> PRO High Capacity cleaning system turns ordinary tap water into stabilized aqueous ozone a longer lasting clean and low slippage on even the smoothest floors. Safe on natural wood and stone.

- Cold tap water enters the lotus<sup>®</sup> PRO Stabilization Module. G
- The lotus® PRO Stabilization Module mixes with the cold tap water stream, expanding the cleaning time up to 24 hours.
- Treated water leaves the lotus<sup>®</sup> PRO Stabilization Module.
- Water passes through the FloJet connector, which prevents backflow with air lock, then enters the lotus<sup>®</sup> PRO High Capacity Unit.
- Oxygen enters the dispenser through the replaceable filter cartridge.
- 4,500 volts of electricity transforms 0, to 0<sub>3</sub>.
- Ozone gas that is not saturated in the water is separated and safely dispensed as oxygen. 6
- Stabilized Aqueous Ozone leaves the dispenser to fill mop buckets, trigger sprayers, and auto scrubbers.
- \* For support reference, visit our website at www.tersano.com US and International Patents and Patent Pending. lotus<sup>®</sup> and Tersano <sup>™</sup> are trademarks of Tersano Inc.



# Product Performance

# TECHNICAL SPECIFICATIONS

30

HIGH CAPACITY UN	HIGH CAPACITY UNIT & STABILIZATION MODULE	DDULE
<b>Dimensions:</b> 17.5" x 14.5" x 7"	14.5″ x 7″	
Weight: 25lbs		
Flow: Continuous - 3	Flow: Continuous - 30 min. shut off safety feature	ure
Rate: up to 3 gals/min	и	
Power: Standard 11(	Power: Standard 110V (Power consumption about 90 watts)	oout 90 watts)
Built-in mechanical backflow prevention	ackflow prevention	
MODEL #	LQFC425K	LQFC825K
Sanitizing Time	Up to 4 hrs	Up to 24 hrs
<b>Cleaning Time</b>	Up to 3 days	Up to 6 days
Cartridge Life	Series I - 1,600 gals <sup>1</sup>	Series II - 800 galls <sup>1</sup>

Max. Water Temp: 65°F 220V versions available

<sup>1</sup> Based on a flow rate of 3 gpm

LQFC425K and LQFC825K includes: lotus<sup>®</sup> PRO High Capacity Unit with Stabilization Module and One (1) desiccant cartridge.



0



# Ozone Laundry Technology & Detergent Program Get with THE PROSGRAM

THE PRO, GRAM by Tersano delivers cleaner, brighter, fresher and softer laundry special cold water ozone boosting detergent, you get better results with less or no for less. By combining our powerful cold water ozone laundry system with our hot water.

levels of ozone during wash and rinse cycles while our uniquely Lifting out the toughest dirt, germs and grime, THE PRO, GRAM gets you out of hot water from high utility bills and gives you THE PRO<sub>3</sub>GRAM's patented ozone system maintains high formulated detergent bolsters ozone's natural cleaning power. outstanding laundry results.



### ی) ج

Reduce or eliminate hot water

BENEFITS

- Safe for workers & environment Reduce drying time Reduce chemical & water consumption
- Eliminate harsh fumes & chemicals
- Decrease wash & rinse cycles
- Installs in 2 4 hours

 Get brighter, fresher, cleaner laundry Increase linen lifespan by up to 30%

Sanitize during wash & rinse

### **Dryer Jack**

- Cuts drying time from 10% to 40%
  - Dramatic energy costs savings
- Prevents bed sheets & towels from

- tangling while being dried

#### LAUNDRY SYSTEM DIMENSIONS

Weight: 300lbs (combined weight of both modules) Electrical Module: 24" x 24" x 12" Water Module: 24" × 20" × 10"

Ozone Generator Output: 16 g/hr Power: 120VAC, 60 Hz, 10.0 Amp

Water Flow: 20 GPM (max)

#### Remove more dirt & grime **Eliminates residue & stains**

Strong yet safe, lotus® PROscrub accelerates the power of the lotus® PRO Cleaning System's patented aqueous ozone technology. Specially formulated for first-time lotus® PRO Cleaning System users, PROscrub lifts years of build-up from chemical residues, dirt, grime and grease in just minutes.

Perfect for any hard surface, ceramic, tile, metal, industrial flooring, equipment, and great for grout and crevices where dirt and grime have built up over time.

LIFTS **BUILD-UP** 





#### **INLINE ON-DEMAND** MODULE

Tersano's inline technology allows the use of ordinary tap water to produce Aqueous Ozone (AO) on-demand.

In ice machines, AO sanitizes the water, ice path and holding bins without chemicals, vastly reducing the risk of foodborne illness associated with unsanitary ice making. For handwashing, our proprietary technology ensures that an effective and consistent level of ozonated water is always produced.

With a minimum of 1.25PPM of sanitizing strength, the AO produced is an approved, proven and powerful natural cleaner that doesn't require costly, toxic chemicals or time-consuming rinsing.

#### TECHNOLOGY

The system is based on time-proven corona discharge technology paired with our patented stabilization system for extended Aqueous Ozone half-life.

Our Aqueous Ozone solution is currently used in many companies and institutions around the world for their cleaning and sanitizing needs.

- Hospitals general use areas
- Schools
- Factories

- Breweries
- Lodaina
- Hospitality



#### **TECHNICAL SPECIFICATIONS**

Dimensions: 4.2" L x 12" W x 8.2" H Weight: 6 lbs **Power Requirements:** Voltage: 24 VDC system - 110/220 VAC adaptor Amperage: 0.2 A Max Water Pressure: 100 PSI Water Flow Rate: 0.5 LPM Max Water Temp: 65°F AO Output: 1.25 ppm





Direct Environmental Corp. • 2929 Third Avenue, 4th Fl, Bronx, NY 10455 • Ph: (718) 607-7658 • Fax: (718) 504-7873 • DECGreen.com For more information contact Frank Cruz: DECalternate@gmail.com

DISTRIBUTED BY